

TECHNICAL DATA SHEET (TDS)


THE TEK

ID Product Code 014

Pag | 1

WAX FOR WOOD

Liquid wax for polishing of wood.



Product description:

THE TEK is a special liquid formulation of noble waxes diluted in solvent for polishing wood. The product gives a warm gloss, enhances colors and is used for polishing floors, furniture in any kind of natural or colored wood. THE TEK is ideal to revive the color and shine of floors and to protect them against wear due to everyday traffic.

Chemical characteristics:

Appearance	Liquid
Color	Opalescent
Odor	Light of solvent
Specific gravity at 20° C (68° F)	0,78 ± 0,05
Hydro-solubility	Not soluble
pH	N.A.
Shelf life at 20°C (68° F)	24 months in original container

Instruction for use

Thoroughly wash the floor, allow the surface to dry for 30 minutes and apply THE TEK with following methods:

Treatment of furniture or antiquity:

Pour a small quantity of product directly on a woolen cloth, or drop a few drops of THE TEK on the material to be treated; spread it homogeneously on the surface with a woolen cloth, let it dry for about 10 minutes and then proceed to polish with a soft clean woolen cloth or suitable electrical tool for furniture polishing.

Treatment of parquet or wood floor:

Pour a few drops of THE TEK directly on a woolen cloth and spread it evenly on the floor; let it dry for about 10 minutes and then polish with a wool cloth or a normal floor-polishing machine equipped with polishing cap.

Application tools



Cloth



Polishing tools



Floor polisher

Suggestion for use and recommendations:

- The longer the wax remains on the surface to be treated, the better will be the result.
- Product for indoor use. Ventilate the premises during application.
- Shake can before use.



DISCLAIMER All data indicated in this leaflet are the results of tests and experiments carried out in our laboratories and through reliable operators in the stone business and have to be considered reliable. Because of the many factors which can influence them, the information here reported do not constitute implicit or formal guarantees. The end user undertakes the responsibility in the usage of the product making sure to experiment the product characteristic as preventive measure.



TDS N°

014

TECHNICAL DATA SHEET (TDS)

- In cold seasons take care to keep the can in a temperate environment (above 15°C - 59°F)
- Read carefully recommendations printed on label and perform a preliminary test on a small area before actual use.

Application surfaces

Pag | 2 Wooden flooring, furniture, decor.

Coverage

With one can of 1 lt. (33 oz.) of product is possible to treat 40/60 sqm (430/650 sq.ft.)

Safety procedures

As far as the proper working procedures is concerned, we recommend to consult Material Safety Data Sheets issued according to E.U. rules and to follow your national laws concerning safety in the working place. MSDS is available on our web site www.bellinzoni.com

Packing

Item N°	Packing	Pcs
014ATEK01	1,00 lt (33,81 fl.oz.)	12

The composition of the tins is Steel (ACC). After use, comply with the local and national regulations currently in force regarding recycling. Our packing is conformed as per U.N. rules for inland transport (A.D.R.) and by sea (I.M.O.) for transportation via air refer to updated rules (I.A.T.A.). For further information regarding transport please check MSDS.

H.S. Code

34.04.9000

Trademark and Origin of the good

BELLINZONI® is a registered trademark of Bellinzoni company. The law considers a trademark to be a form of property and any misuse can be persecuted by law. Bellinzoni s.r.l. declares that our product THE TEK is **MADE IN ITALY**.



DISCLAIMER All data indicated in this leaflet are the results of tests and experiments carried out in our laboratories and through reliable operators in the stone business and have to be considered reliable. Because of the many factors which can influence them, the information here reported do not constitute implicit or formal guarantees. The end user undertakes the responsibility in the usage of the product making sure to experiment the product characteristic as preventive measure.



TDS N°

014